

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 952 744 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.10.1999 Bulletin 1999/43

(51) Int Cl.⁶: H04Q 7/22, H04Q 7/24,
H04Q 7/38, H04Q 3/00

(21) Application number: 99303149.1

(22) Date of filing: 23.04.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 23.04.1998 GB 9808725
23.04.1998 GB 9808723

(71) Applicant: NORTel NETWORKS CORPORATION
Montreal, Quebec H2Y 3Y4 (CA)

(72) Inventors:
• Joly, Celine Aline Paulette
Maidenhead, Berkshire SL6 4JP (GB)
• Pham, Thanh
Plano, Texas 75024 (US)

• Candish, John
London W4 4QS (GB)
• Fuller, Jeremy
Maidenhead, Berkshire SL6 4EB (GB)
• Sharp, Iain
Maidenhead, Berkshire SL6 5DD (GB)
• Scheving, Michaela
Richardson, Texas 75080 (US)
• Le, Khuong Quang, c/o Nortel Technology Inc.
Richardson, Texas 75082-4399 (US)


(74) Representative:
Humphrey-Evans, Edward John et al
Nortel Networks
Intellectual Property Law Group
London Road
Harlow, Essex CM17 9NA (GB)

(54) A mobile telecommunications system supporting the use of functional numbers

(57) The present invention relates to specialised mobile communication schemes which are becoming frequently deployed, for example, utility mobile communication schemes such as railway-operator-consortia-managed mobile communications schemes which come under the umbrella term of GSM-Railways (GSM-R) systems. The invention seeks to define an architecture to support the use of 'Functional Numbers' for addressing purposes within a wireless communication network,

and provide a method for transporting 'Functional Numbers' between the relevant wireless communication entities within the architecture. The invention also seeks to define a flexible and extendible encoding scheme for the GSM-R defined supplementary service handling operations used for registering, interrogating and deregistering FNs. In addition the invention provide an extension to the way Functional Numbers are registered and deregistered by providing an encoding for supervisory control of registration and deregistration procedures.

Figure 1



Description

FIELD OF THE INVENTION

[0001] The present invention relates to mobile communications systems and, in particular, although not restricted to such, relates to a utility communications system.

BACKGROUND OF THE INVENTION

[0002] Wireless mobile telecommunication services are now quite commonplace. There are in existence worldwide several wireless mobile telephony standards which are provided for general public use, by way of subscription or similar. Many advantages of mobile wireless telephony exist over standard fixed line POTS telephony systems, the most significant being that the mobile telephone is mobile as such, provided that the use of a particular mobile telephone corresponds within a region covered by the operator to which the mobile subscriber is connected to.

[0003] Specialised mobile communication schemes are also becoming more frequently deployed. A number of bodies are defining requirements and standards for utility mobile communication schemes for Railway systems. These include the Mobile Radio for Railway Networks in Europe (MORANE) group, a consortium of European railway operators and equipment manufacturer with European Union funding who are defining a pan-European standard. The MORANE standard specifies extensions to the Global System for Mobile Communications (GSM) standard for application in the Railways environment. Other bodies involved in specifying requirements or standards in this area include EIRENE and ETSI itself. The term GSM-Railways (GSM-R) has been adopted as an umbrella term to cover all Railway system schemes. For simplicity, in the description of the prior art and the invention, reference shall be made to GSM-R systems and in particular the MORANE standard, but it is to be understood that the scope of the claims are not to be limited to such and is applicable to all GSM/GSM-R derivative systems.

[0004] In a GSM-Railway network, communication is required between different user types (person to person, person to system, system to system) in different environments (on the same train, from train to train, from/to ground to/from train, from ground to ground). The different user types need to be able to communicate with each other using special railway numbers, i.e. Functional Numbers (FN) which reflect functional information such as the train number the user is on, the function of the train (goods or passenger), the function of the person who is assigned a particular GSM-R phone etc. A central register, known as the Functional Home Location Register (HLRF), stores the Functional Numbers and their related data. An access matrix function which provides means of checking which person call another one,

is located on the central functional register. The intention is to enable GSM-R personnel and systems to use the Functional Number instead of the GSM Mobile Station ISDN number (MSISDN) for dialling and display purposes.

[0005] In order for this to work a service called 'Follow Me' has been specified, which allows a MS user to register a temporarily assigned FN against a temporarily assigned MS, and deregister the association once he no longer requires either the FN or the MS. For example when a train operator starts working on a train or in a station, he needs to be able to enter the FN he has been assigned for the journey or for the day on the particular mobile station (MS) he is going to use, and have that association stored in a central register associated with the system. Any calls to the FN need access to the central register to determine which MS the train operator is using and therefore where to route the call. The train operator needs to be able to check the status of the FN by performing an interrogation sequence, and when the train operator has finished working with his assigned MS, he needs to be able to de-register the FN.

[0006] Relationship of FN to Railway Access Code and Railway Subscriber Number would be as follows:

FN =

Railway Subscriber Number + Railway Access code

[0007] Currently in a GSM network a calling subscriber uses a called subscribers Mobile Subscriber ISDN number (MSISDN) for call set-up purposes. This is used to route a call to a Gateway Mobile Switching Centre (GMSC) which interrogates the Home Location Register (HLR) for a routing number. The routing number returned by the HLR is used to route the call through the GSM network to the called subscriber.

[0008] The GSM-Railways requirement to use a Functional Number, which cannot be used for routing purposes, means that the originating switch must somehow use the called FN to obtain the called users MSISDN from a central functional register before it can set-up the call. It must also provide the calling FN to the access matrix for validation. Currently there is no standard architecture to do this or any mechanism to transport the called party FN and calling party FN to the access matrix function

[0009] The GSM-R solutions for allowing railway personnel to register and deregister FNs with the access matrix do not include any flexibility in the types of registration and deregistration available. Disadvantages of the current GSM-R solutions include the fact that there is no way of registering FNs for Fixed Line Directory Numbers (DN) and that the system does not allow deregistration to be performed from terminals other than the terminal used for registration. Further, the system does not include any extensibility, such that any future requirement for additional types of registration, interro-

gation or de-registration procedures would require significant software development.

OBJECT OF THE INVENTION

[0010] The invention seeks to define an architecture to support the use of 'Functional Numbers' for addressing purposes within a wireless communication network, and provide a method for transporting 'Functional Numbers' between the relevant wireless communication entities within the architecture.

[0011] The invention also seeks to define a flexible and extendible encoding scheme for the GSM-R defined supplementary service handling operations used for registering, interrogating and deregistering FNs. In addition the invention provide an extension to the way Functional Numbers are registered and deregistered by providing an encoding for supervisory control of registration and deregistration procedures

STATEMENT OF THE INVENTION

[0012] In accordance with a first aspect of the invention, there is provided in or for a GSM-based telecommunications system an architecture for providing call set up procedures, the architecture employing an access matrix at a Service Control Point (SCP), wherein the architecture further comprises: the use of GSM/ ISDN User-to-User supplementary service protocols and IN protocols to transport FNs between an originating switch and the access matrix; and an information analysis trigger means at a detection point; wherein a routing and alerting means associated with the detection point routes and alerts the network of the originating basic call and the Initial detection point message between the GMSC and the SCP; and routes from the SCP to the GMSC a connect message when connection is possible. Preferably a release call message is issued when connection is not possible.

[0013] Preferably the architecture defines an Intelligent Network (IN) architecture which sites the access matrix at a Service Control Point (SCP). Preferably transport of the FNs between the originating switch (i.e. GMSC) and the access matrix (sited at the SCP) is enabled by means of a user-user IE and a calling party sub-address parameter. The calling party subaddress could be provided by means of an Intelligent Network parameter.

[0014] The system could support an Unstructured Supplementary Service Data protocol and which would provide an encoding mechanism for supporting supplementary service handling operations which mechanism provides supervisory control.

[0015] In accordance with another aspect of the invention, there is provided, in or for a GSM-based telecommunications system comprising an architecture which employs an access matrix at a Service Control Point (SCP), a method of providing call set up proce-

dures, the method comprising:

transporting FNs between an originating switch and the access matrix using a user-user interface element and an calling party subaddress;

triggering information analysis on reaching the detection point ;

routing and alerting in the network the originating basic call state machine the Initial detection point message between the GMSC and the SCP; and

routing from the SCP to the GMSC a connect message when connection is possible. Preferably a release call message is issued when connection is not possible.

[0016] Preferably the method comprises the following procedures:

i. the deployment of standard GSM/ MORANE procedures used by the calling subscriber to originate a call;

ii. the deployment of standard GSM/ MORANE procedures used by MSC to accept the call set-up and invoke the originating basic call state machine;

wherein upon reaching Detection Point 3 in the originating basic call state machine, the following procedures are triggered:

iii. the transportation of called and calling functional number to the SCP;

iv. the transportation of successful or unsuccessful results back to the MSC

whereupon standard GSM/ MORANE procedures may be employed to continue using the returned data .

[0017] In accordance with a further aspect of the invention, there is provided a supervisory management registration class of GSM-R MSs operable in or for a GSM-based telecommunications system supporting an Unstructured Supplementary Service Data protocol to provide enhancement of the use of USSD strings for the registration, interrogation and deregistration operations, extensibility and introduction of new fields, wherein a user having such a supervisory management registration class is capable of registering and deregistering other users.

[0018] In accordance with a still further aspect of the invention, there is provided in or for a GSM-based telecommunications system comprising an architecture which employs an access matrix and utilises the GSM Unstructured Supplementary Service Data protocol, a flexible and extendible encoding scheme for the GSM-

R defined supplementary service handling operations used for registering, interrogating and deregistering FNs. The encoding scheme introduces a number of fields for use in a USSD string: a first field indicating the general operation code (registration, interrogation and de-registration); a second field indicating the service code; a third field indicating the service type of the operation; and a fourth field indicating a list of parameters, wherein the third field parameters can be entered as a number between 1 and 9; and the fourth field parameters can vary for each string and operation. The field indicating the general operation code has two or three characters.

[0019] The two fields which describe an operation provide flexibility. If the operation service type was introduced at the very beginning, it could interfere with service codes other than the FM service, blocking some possibilities in the use of the operations. Different service codes (including GSM service codes) could be used with the general operations, without being excluded by a too specific operation which would block access to other services. To provide full flexibility in the use of the operations, the operation service type is preferably introduced after the service code field. A further field comprising a separation character (*) can be interposed between information fields.

[0020] Preferably, the GSM Unstructured Supplementary Service Data (USSD) protocol string comprises the following fields:

1. A first field indicating the general operation code (registration, interrogation and deregistration);
2. A service code ;
3. A separation character (*);
4. The service type of the operation,
5. A separation character (*);
6. A list of parameters for each string and operation;
7. An ending character (#).

[0021] The user who registers or de-registers other people than himself via Supervisor registration or Supervisor de-registration must use a mobile station that has a class of registration which reflects the supervisory management status. A class of registration (value "E") is provided which is a supervisor's registration/de-registration class.

[0022] In accordance with a further aspect of the invention, there is provided in or for a GSM-based telecommunications system comprising an architecture which utilises the GSM Unstructured Supplementary Service Data protocol, an encoding mechanism for supporting supplementary service handling operations

which provide supervisory control for registration and deregistration procedures.

[0023] Preferably the supervisory handling operations include registration and deregistration of functional numbers of a user whereby the user can be associated and deregistered with respect to a MSISDN by a supervisor.

BRIEF DESCRIPTION OF THE FIGURES

[0024] In order that the present invention can be more fully understood and to show how the same may be carried into effect, reference shall now be made, by way of example only, to the Figures as shown in the accompanying drawing sheets wherein:

Figure 1 shows the Functional Architecture of a GSM-R network

Figure 2 shows the Proposed GSM-R Architecture for the Invention

Figure 3 shows the Messages and Parameters used to transport FN's during call set-up.

Figure 4 shows the Four USSD strings used for the Follow Me service and their length limits.

Table A shows the parameters used in the transport of FNs across the network for each message involved in the process.

Table 1 shows the function of Class of registration.

Table 6 shows the possible USSD responses that may be provided in string 3 and string 4 applicable to Follow me, and also lists examples of the text messages that can be displayed on the MS once the translation of the outcome code has taken place in the MS.

Tables 2 - 15 (except Table 6) show the content of each string for each procedure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0025] There will now be described, by way of example, the best mode contemplated by the inventors for carrying out the invention. In the following description, numerous specific details are set out in order to provide a complete understanding of the present invention. It will be apparent, however, to those skilled in the art that the present invention may be put into practice with variations of the specific.

[0026] Figure 1 shows an overview of a GSM-Railways private network. The call area is indicated by the track 20 and outlying area 22, upon which track trains 24 operate in communication with GSM-R subscribers and dispatchers 26 (associated with both mobile and fixed stations) while in the coverage area of the GSM-R system.

[0027] Within GSM-R systems Functional Numbers (FNs) have been defined for identification and setting up communication between different GSM-R user types. An access matrix function has been defined (in the HLRf) to validate associations between FNs and specific MS equipment, and to control which user categories can call each other (MORANE SSRS A 04/02 T 6002). A service, called Follow Me, has been defined to enable GSM-R personnel to be contacted using a FN (rather than the telephone number of the MS they are using) and a way of registering and deregistering FNs in the HLRf from the MS has been defined in order for the service to be activated or deactivated. However there is currently no standardised way for GSM-R systems to actually implement the access matrix function; there is no standardised mechanism to transport the called party FN and calling party FN to the access matrix function in order to be processed before a call set-up attempt is made; and lastly, there is no capability for supervisory registration/ deregistration of FNs in the access matrix.

[0028] The first aspect of the invention (i.e. defining an architecture to support the use of FNs for addressing purposes) sites the HLRm and HLRf functions of a GSM-R system in the HLR and SCP network entities respectively (see Figure 2). The advantages of this solution include the technical benefits provided by IN, both for the initial implementation and any future extension/ enhancement.

[0029] Transport of the FNs between the originating switch (i.e. GMSC) and the access matrix (sited at the SCP) is triggered on reaching Detection Point 3 (Detection Point which analyses information before routing and alerting in the Intelligent Network) in the originating basic call state machine. The IN message used between the GMSC and the SCP is the Initial DP message, and from the SCP to the GMSC the Connect message is used in successful cases and the Release call message is used in unsuccessful cases (when the call will have been rejected as the result of the access matrix check).

[0030] The information flow for a call set-up is:

1. Standard GSM-R procedures used by the calling subscriber to originate a call
2. Standard GSM-R procedures used by GMSC to accept the call set-up and invoke the originating basic call state machine.
3. Invention triggered on reaching Detection Point 3 in the originating basic call state machine.
4. Invention transports called and calling functional number to the SCP
5. Invention transports successful or unsuccessful results back to the MSC
6. Standard GSM/ MORANE procedures continue

using the returned data (i.e. continue with call set-up or fail the call attempt).

[0031] The second aspect of the invention (i.e. providing a method for transporting FNs between network entities) utilises the ISDN and GSM User-to-User Signalling Service, and the ITU IN protocol. The following table and information flow diagram (Figure 3) show how the FNs are obtained and transported to and from the access matrix during the GSM-R call set-up procedure:

[0032] The third aspect of the invention (i.e. extending the USSD encoding to provide flexibility for GSM-R defined supplementary service handling operations used for registering, interrogating and deregistering FNs) defines a range of fields for use in a USSD string (Table 2). This range of fields and the encoding used provides a flexible and extendible mechanism to support the registration, interrogation and de-registration operations and any future operations which may be required. The following fields are defined: (Note: fields 1-3 existing, fields 4 & 6 part of the invention)

1. The general operation code (registration, interrogation and de-registration);
2. The service code (which can be FM or another service);
3. A separation character (*);
4. The service type of the operation (entered as a number between 1 and 9);
5. A separation character (*);
6. List of parameters (a variable dependent upon string type and operation - see tables later);
7. Ending character (#).

[0033] The aim of the two fields which describe an operation (1 and 4) is to introduce flexibility. If the operation service type was introduced at the very beginning, it could interfere with service codes other than the FM service, blocking some possibilities in the use of the operations. Different service codes (including GSM service codes) could be used with the general operations, without being excluded by a too specific operation which would block access to other services. To provide full flexibility in the use of the operations, the operation service type is preferably introduced after the service code field.

[0034] No separation field between the operation code and the service code is required because the operation code will always be a combination of * and #, thus the first number of the service code determines the end of the operation code. Between the other fields a separation character can be inserted to comply with GSM 02.90 (USSD) and GSM 02.30 (MMI) and is also

a more user friendly way to key in the commands by the user.

[0035] The first field, Operation, has two or three characters and allows for future creation of operations, combining * and # over three characters.

[0036] The fourth aspect of the invention (i.e. providing a solution for supervisory control of FN registration and deregistration procedures) defines a new MS Registration Class of 'E' (registration/ deregistration supervisors) which is stored in the HLRm (see Table 1) and checked on receipt of a registration/ deregistration request which includes a 'supervisor' category code.

[0037] In the table section, showing the format and content of USSD strings for each of the supplementary service operations (registration, interrogation, and deregistration) are given. The table notation is:

M for fields which are mandatory for the execution of the operation.

O for fields which are optional for the execution of the operation.

C for fields which are conditional for the execution of the operation and will be detailed in a note wherever used.

E for fields which show when extensibility is being proposed, so that there is no barrier for future enhancement, for instance: the creation of new service type for the operations.

[0038] An example will be given for each of the 4 strings used to perform an operation (see Figure 4).

[0039] Table 3 shows a proposed registration USSD string 1 content (MS to HLRm).

[0040] Examples of string 1 registration follow:

**10*88824567890101# => A user registers FN 888 2 45678901 01 against the MSISDN he is using, without service type indication.

**10*1*88824567890101# => A user registers his own FN against the MSISDN he is using with service type indication.

**10*888965432*33329450532#

[0041] User registers controllerl with FN 888 9 6543 2 against DN 33 329 450532 (without category indication). This is allowed only if registration is activated from a MS with class of registration E.

**10*3*888965432*33329450532# (supervisor registration)

[0042] From his MS a user registers controllerl with Functional Number 888 9 6543 2 against a fixed line terminal

with DN = 33 329 450532 (with category indication). The MS used to request the registration must have class of registration E.

[0043] Table 4 shows a registration USSD string 2 content (HLRm to HLRf), examples of such being:

**10*1*88824567890101*44802567123# => A user registers FN 888 2 45678901 01 against the MSISDN he is using and the served/ associated MSISDN is transferred to the HLRf:

**10*3*33329450532*88824567890133*44802567123# => Supervisor registration: From his MS, a user registers FN 888 2 45678901 33 against his fixed line colleague with DN = 33 329 450532, using an MS with the served MSISDN 44 802 567123.

[0044] Tables 5 and 7 show a proposed registration USSD strings 3 and 4 contents (HLRf to HLRm, followed by HLRm - MS). Examples of which are:

00 (space) USSDResponse. => Successful registration. In a successful case, a message may optionally be sent inside the USSDResponse field, such as 'registered'.

06 (space) USSDResponse. => Unsuccessful registration.

[0045] For the case where the FN is already registered, the message 'already registered' may be sent to the MS.

[0046] It is the MS role to translate the outcome code into the appropriate message to be displayed on the handset screen. Some examples of messages that can be displayed are shown in Table 6.

Interrogation

[0047] Interrogation of a single FN is performed to obtain its associated MSISDN/ DN (for fixed terminals).

[0048] Table 8 shows a proposed interrogation USSD string 1 content (MS to HLRm), an example of which is:

#10/1/*77729876543210# => User interrogates driver2's FN (777 2 98765432 10). /* is optional.

[0049] Table 9 shows a proposed interrogation USSD string 2 content (HLRm to HLRf), an example of which is:

*#10*1*77729876543210*44802567123# => User on MSISDN 44 802 567 123 interrogates FN 777 2 98765432 10.

[0050] Tables 10 and 11 show a proposed interrogation USSD strings 3 and 4 contents (HLRf to HLRm, followed by HLRm - MS). Examples of which are:

20 (space) USSDResponse. => Successful interrogation. In a successful case, a message may optionally be sent inside the USSDResponse field as well as the result itself of the interrogation (i.e. the forwarded to number associated with the FN).

24 (space) USSDResponse. => Unsuccessful interrogation.

[0051] For the case where the FN is not registered, the message 'FN not registered' may optionally be sent to the MS.

[0052] It is the MS role to translate the outcome code into the appropriate message to be displayed on the handset screen. Some examples of messages that can be displayed are shown in Table 6.

[0053] The associated MSISDN/ DN is the forwarded to number to which the FN being interrogated is registered to and is not to be confused with the served MSISDN from where the interrogation is performed. The interrogation response is conditional, it is not mandatory when interrogation cannot be activated (there is an error), but it is mandatory when interrogation has been activated i.e. the MSISDN corresponding to the FN interrogated must be included in response string 4.

De-registration

[0054] Currently MORANE describes the following de-registration: the user de-registers his own FN using the MS which was used to register the FN. This is the first optional service type: user de-registration. Greater variety and flexibility to de-registration is possible, allowing a user to de-register another user within GSM-R or all users of the same train at the same time.

[0055] The person performing de-registration on others' FNs must be entitled to do so, and his identity and eligibility for de-registration (supervisor and global) should be checked in the HLRm where the class of registration check will take place. A new class of de-registration "E" is introduced for supervisory management status.

[0056] Three optional service types for de-registration are possible: User De-registration : Single FN de-registration activated from the MS associated with the FN to be de-registered. Global De-registration : De-registration of all FNs of one train from a MS with class of registration E. Supervisor De-registration : De-registration of FN(s) from a MS with class E registration.

[0057] The service types are optional as some operators may not wish to use them, but they are created to bring more variety and flexibility to the de-registration operation. When service types are not used, de-registration entitlement will be checked by the class of registration check at the HLRm and the FN - MSISDN association check at the HLRf. When service types are used they limit the use of de-registration, which makes all the possibilities for de-registration less ambiguous to use.

[0058] Table 12 shows a proposed de-registration USSD string 1 content (MS to HLRm), examples of which are:

5 ##10*88824567890101# => Without any service type indication, this command means that the user wants to de-register FN 88824567890101. If the FN is associated with the MS activating de-registration, de-registration of the user is performed: if this FN is a lead train driver's FN, all the MSs on the train will be de-registered at the same time: If the FN is not associated with the MS activating de-registration, de-registration of the FN (and all other FNs on the train if the MS is that of, for example, the lead train driver's FN) is only possible if the MS has a registration class E.

10 ##10*1*88824567890101# => User de-registration: With a service type 1 command the user can de-register only himself (even if it is a lead train driver's FN), the FN needs to be his own FN associated with the MS on which he is activating the de-registration.

15 ##10*2*88824567890101# => Global de-registration: With a service type 2 command the user can de-register everybody on the train who has the same running number as the lead train driver (45678901). If the FN is associated with the MS activating de-registration is a lead train driver's FN, all the MSs on the train will be de-registered at the same time i.e. global de-registration can be performed. If the FN is not associated with the MS activating de-registration, then global de-registration can only be performed if the MS has a registration class E.

20 ##10*3*77729876543210# => Supervisor de-registration: With a service type 3 command the user can register only one other user. The MS activating supervisor de-registration must have a registration class E.

25 **[0059]** Note: this will de-register ONLY FN 777 2 98765432 10 (even if it is a lead train driver's FN). Global de-registration by a supervisor shall be done using category 2, or with no category indication.

30 **[0060]** The person who wants to de-register other users will be recognised by his MSISDN and the class of registration it carries. The HLRm will determine if the person requesting global or supervisor de-registration is entitled to activate it, checking the class of registration (users with the class E registration will be allowed to activate de-registration). For user de-registration, the FN entered here is the FN of the user who wants to de-register himself. For supervisor de-registration, the FN entered here is the FN of the other person that the user wants to de-register. For global de-registration, the FN

entered here is the lead train driver's FN, as the train driver FN always contains the running number which will be used to apply global de-registration on every FN carrying the same RN as the driver.

[0061] Table 13 shows a proposed de-registration USSD string 2 content (HLRm to HLRf), examples of which are:

##10*1*88824567890101*44802567123# => User de-registration: In the case that a user with MSISDN 44 802 0567123 wants to de-register himself only and his MSISDN is sent to the HLRf, then this string applies.

##10*2*88824567890101*44802567123# => Global de-registration: If the user wants to de-register everybody registered on the train with running number 45678901 and his MSISDN is sent to the HLRf, then this string applies.

##10*3*77729876543210*44802567123# => Supervisor de-registration: If the user wants to de-register only driver2 on train 98765432 and his MSISDN is sent to the HLRf, then this string applies.

[0062] Tables 14 and 15 show a proposed de-registration USSD strings 3 and 4 contents (HLRf to HLRm, followed by HLRm - MS). Examples of which are:

10 (space) USSDResponse. => Successful de-registration. In a successful case, a message may optionally be sent inside the USSDResponse field, such as 'deregistered'.

[0063] User de-registration: A user can de-register himself. The de-registration can be carried out by service type 1 in string 1, or without the service type indication. In the latter case, either the FN is associated with an MS capable of activating de-registration or if the FN is not associated with the MS activating de-registration and the MS has a registration class E, e.g. for arbitrary FN.

[0064] Global de-registration: A user can de-register FN 888 2 45678901 01 and all FNs on the same train with running number 45678901. The de-registration could be achieved with service type 2 in string 1, or without the service type indication. In the latter case, either the FN is associated with an MS capable of activating de-registration or if the FN is not associated with an MS capable of activating de-registration and the MS has a registration class E.

[0065] Supervisor de-registration: User can de-register driver2 only on other train. The de-registration can be carried out with service type 3 in String 1 or with no service type indication. In both cases the MS must have a registration class E.

14 (space) USSDResponse. => Unsuccessful de-

registration.

[0066] For the case where the FN is not registered, the message 'FN not registered' may be sent to the MS

[0067] It is the MS role to translate the outcome code into the appropriate message to be displayed on the handset screen. Some examples of messages that can be displayed are shown in Table 6.

Claims

1. In or for a GSM-based telecommunications system an architecture for providing call set up procedures, the architecture employing an access matrix at a Service Control Point (SCP), the architecture further comprising:

user-user interface element means and a calling party subaddress means to transport FNs between an originating switch and the access matrix;

an information analysis trigger means at a detection point;

wherein a routing and alerting means associated with the detection point routes and alerts the network of the originating basic call and the Initial detection point message between the GMSC and the SCP; and routes from the SCP to the GMSC a connect message when connection is possible.

2. An architecture according to claim 1 wherein means are provided to issue a release call message when connection is not possible.
3. An architecture according to claim 1 or 2 wherein the architecture defines an Intelligent Network (IN) architecture which sites the access matrix at a Service Control Point (SCP).
4. An architecture according to any one of claims 1 - 3 wherein transport of the FNs between the originating switch (i.e. GMSC) and the access matrix (sited at the SCP) is enabled by means of a user-user IE and a calling party subaddress.
5. An architecture according to claim 4 wherein the calling party subaddress is provided by means of an Intelligent Network parameter.
6. A architecture according to any one of claims 1 - 5, wherein the system is capable of supporting an Unstructured Supplementary Service Data protocol and wherein there is provided an encoding mechanism for supporting supplementary service han-

dling operations which mechanism provides supervisory control.

7. A architecture according to claim 6 wherein the supervisory handling operations include registration and deregistration of functional numbers of a user whereby the user can be associated and deregistered with respect to a MSISDN by a supervisor. 5
8. In or for a GSM-based telecommunications system comprising an architecture which employs an access matrix at a Service Control Point (SCP), a method of providing call set up procedures, the method comprising: 10
 - transporting FNs between an originating switch and the access matrix using a user-user interface element and an calling party subaddress; 15
 - triggering information analysis on reaching the detection point ; 20
 - routing and alerting in the network the originating basic call state machine the Initial detection point message between the GMSC and the SCP; and 25
 - routing from the SCP to the GMSC a connect message when connection is possible. 30
9. A method according to claim 8 wherein a release call message is issued when connection is not possible.
10. A method according to claim 8 wherein the method comprising the following procedures: 35
 - i. the deployment of standard GSM/ MORANE procedures used by the calling subscriber to originate a call; 40
 - ii. the deployment of standard GSM/ MORANE procedures used by MSC to accept the call set-up and invoke the originating basic call state machine; 45
 - wherein upon reaching Detection Point 3 in the originating basic call state machine, the following procedures are triggered: 50
 - iii. the transportation of called and calling functional number to the SCP;
 - iv. the transportation of successful or unsuccessful results back to the MSC 55

whereupon standard GSM/ MORANE procedures may be employed to continue using the returned

data .

11. A method according to claim 10 wherein a release call message is issued when connection is not possible.
12. A supervisory management registration class of GSM-R MSs operable in or for a GSM-based telecommunications system supporting an Unstructured Supplementary Service Data protocol to provide enhancement of the use of USSD strings for the registration, interrogation and deregistration operations, extensibility and introduction of new fields, wherein a user having such a supervisory management registration class is capable of registering and deregistering other users.




Figure 4

Figure 1






FIGURE 3




FIGURE 2

Table A

Msg No.	Msge title	Numbers involved	Number description and transfer requirement for each message
1	Setup (MS to network)	called FN	The calling user dials the called FN which is included in the called party number parameter by the originating switch (ISDN or GSM-R)
		calling FN	The calling FN is currently sent in UUS for display to the called party. The invention requires that the calling FN is always included in the UUS to the GMSC. The UUS format for transporting the calling FN is defined below.
2	Initial Detection Point (GMSC to access matrix)	called FN	The invention requires that the called FN is included in the Initial DP in order to direct the call to the destination and translate it to its corresponding called MSISDN or ISDN number in the HLRf. The invention uses the Called Party Number parameter.
		calling FN	The invention requires that the calling FN is sent to the HLRf to be used in the access matrix to check if the call is allowed. The invention uses the Calling Party Subaddress parameter.
3	Connect (access matrix to GMSC)	called MSISDN or ISDN number	The called MSISDN or called ISDN is provided by the HLRf following translation of the called FN. It is sent to the GMSC to route the call. The invention uses the Destination Routing Address parameter.
		calling FN called FN	The FNs do not need to be sent back to the GMSC since they have not been modified.

3a	Release Call	cause value	Only the cause value parameter is sent back.
4	Setup (Network to MS)	calling FN	The calling FN is sent in a UUS parameter for display to the called party.
		called MSISDN /ISDN No	The called MSISDN or called ISDN number is included in the called party number parameter and used to route the call to the called terminal.
4a	Release Complete	cause value	The calling FN can be sent back to the calling party in the UUS parameter.

Table 1 - Example of Function of Registration Class

Class of Registration	Meaning
A	Engine/Train cab-radio basic functions
B	Maintenance service user
C	Operation support user
D	Customer support users
E	Registration/ De-registration supervisors

Table 2

Operation name Service type	Registration (**)	Interrogation (*#)	De-registration (##)	FFE (...)
1	User	Single	User	FFE
2	FFE	FFE	Global	FFE
3	Supervisor	FFE	Supervisor	FFE
9	FFE	FFE	FFE	FFE

FFE: For future enhancements

Table 3

Operation code (** for registration)	E -M	2-3 characters
Service code (10 for FM service)	M	2-3 characters
Separation field character (*)	O	1 character
Operation category (1 for user registration, 3 for supervisor registration)	O	1 character
Separation field character (*)	M	1 character
Functional Number (FN) to register	M	4-15 characters
Separation field character (*)	C	1 character
Associated DN/MSISDN (MSISDN or Directory Number (DN) to be given a FN, when different than the served MSISDN)	C	4-15 characters
Ending character (#)	M	1 character

Table 4

Operation code (** for registration)	E -M	2-3 characters
Service code (10 for FM service)	M	2-3 characters
Separation field character (*)	M	1 character
Operation service type (1 for user registration, 3 for supervisor registration)	M	1 character
Separation field character (*)	M	1 character
Functional Number FN to register	M	4-15 characters
Separation field character (*)	C	1 character
Associated DN/MSISDN (MSISDN or Directory Number (DN) to be used as forward-to number, when different than the served MSISDN)	C	4-15 characters
Separation field character (*)	M	1 character
Served MSISDN (also forward-to number for user registration and some cases of supervisor registration)	M	4-15 characters
Ending character (#)	M	1 character

Table 5 (This table also corresponds to Tables, 7, 10, 11, 14 and 15):

Outcome code	M	2 characters
Separation field character (space)	O	1 character
USSD Response	O	n characters

Table 6

Registration			
Successful case	USSD response	Display on MS	Outcome Code
Follow me activated	Follow me activated	Follow me activated	00
Error codes	USSD response	Display on MS	Outcome Code
UnknownSubscriber	Wrong MSISDN	Wrong MSISDN	01
IllegalSS-Operation	Request rejected	Request rejected - Call operator	02
SS-SubscriptionViolation	Wrong MSISDN or feature not provisioned	Wrong MSISDN or Feature not provisioned	03
Conditional forwardings active (SS-Incompatibility)	Check conditional forwardings	Check conditional forwardings / Call Operator	04
Call barring active (SS-Incompatibility)	Check Barrings	Check Barrings /Call Operator	05
FunctionalNumberAlready Registered	Functional number already registered	Functional number already registered	06
Deregistration			
Successful case	USSD response	Display on MS	Outcome Code
Follow me deactivated	Follow me deactivated	Follow me deactivated	10
Error codes	USSD response	Display on MS	Outcome Code
UnknownSubscriber	Wrong MSISDN	Wrong MSISDN	11
IllegalSS-Operation	Request rejected	Request rejected - Call operator	12
SS-SubscriptionViolation	Wrong MSISDN or feature not provisioned	Wrong MSISDN or Feature not provisioned	13
Functional number not registered	Functional number not registered	Functional number not registered	14
Interrogation			
Successful case	USSD response	Display on MS	Outcome Code
Forwarded to Number	Forwarded to Number	'Forwarded to Number' digits	20
Error codes	USSD response	Display on MS	Outcome Code
UnknownSubscriber	Wrong MSISDN	Wrong MSISDN	21
IllegalSS-Operation	Request rejected	Request rejected - Call operator	22
SS-SubscriptionViolation	Wrong MSISDN or feature not provisioned	Wrong MSISDN or Feature not provisioned	23
Functional number not registered	Functional number not registered	Functional number not registered	24

Table 8

Operation code (*# for interrogation)	E -M	2-3 characters
Service code (10 for FM service)	M	2-3 characters
Separation field character (*)	M	1 character
Operation service type (1 for single interrogation of FN)	O	1 character
Separation field character (*)	O	1 character
Functional Number (F) to be interrogated	M	4-15 characters
Ending character (#)	M	1 character

Table 9

Operation code (*# for interrogation)	E -M	2-3 characters
Service code (10 for FM service)	M	2-3 characters
Separation field character (*)	M	1 character
Operation service type (1 for single interrogation of FN)	M	1 character
Separation field character (*)	M	1 character
Functional Number (FN) to be interrogated	M	4-15 characters
Separation field character (*)	M	1 character
Served MSISDN	M	4-15 characters
Ending character (#)	M	1 character


Table 12

Operation code (## for de-register)	E -M	2-3 characters
Service code (10 for FM service)	M	2-3 characters
Separation field character (*)	M	1 character
Operation service type (1 for user de-registration, 2 for global de-registration, 3 for supervisor de-registration)	O	1 character
Separation field character (*)	O	1 character
Functional Number FN	M -C	4-15 characters
Ending character (#)	M	1 character

Table 13

Operation code (## for de-register)	E -M	2-3 characters
Service code (10 for FM service)	M	2-3 characters
Separation field character (*)	M	1 character
Operation service type (1 for user de-registration, 2 for global de-registration, 3 for supervisor de-registration)	M	1 character
Separation field character (*)	M	1 character
Functional Number FN	M	4-15 characters
Separation field character (*)	M	1 character
Service MSISDN	M	4-15 characters
Ending character (#)	M	1 character

THIS PAGE BLANK (USPTO)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 952 744 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
20.12.2000 Bulletin 2000/51

(51) Int Cl.7: H04Q 7/22, H04Q 7/24,
H04Q 7/38, H04Q 3/00

(43) Date of publication A2:
27.10.1999 Bulletin 1999/43

(21) Application number: 99303149.1

(22) Date of filing: 23.04.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 23.04.1998 GB 9808725
23.04.1998 GB 9808723

(71) Applicant: Nortel Networks Limited
Montreal, Quebec H2Y 3Y4 (CA)


(72) Inventors:
• Joly, Celine Aline Paulette
Maidenhead, Berkshire SL6 4JP (GB)
• Pham, Thanh
Plano, Texas 75024 (US)

• Candish, John
London W4 5LG (GB)
• Fuller, Jeremy
Maidenhead, Berkshire SL6 4EB (GB)
• Sharp, Iain
Maidenhead, Berkshire SL6 5DD (GB)
• Scheving, Michaela
Richardson, Texas 75080 (US)
• Le, Khuong Quang
Plano, Texas 75093 (US)

(74) Representative: Bewley, Ewan Stuart et al
Nortel Networks
Intellectual Property Law Group
London Road
Harlow, Essex CM17 9NA (GB)

(54) A mobile telecommunications system supporting the use of functional numbers

(57) The present invention relates to specialised mobile communication schemes which are becoming frequently deployed, for example, utility mobile communication schemes such as railway-operator-consortia-managed mobile communications schemes which come under the umbrella term of GSM-Railways (GSM-R) systems. The invention seeks to define an architecture to support the use of 'Functional Numbers' for addressing purposes within a wireless communication network, and provide a method for transporting 'Functional Numbers' between the relevant wireless communication entities within the architecture. The invention also seeks to define a flexible and extendible encoding scheme for the GSM-R defined supplementary service handling operations used for registering, interrogating and deregistering FNs. In addition the invention provide an extension to the way Functional Numbers are registered and deregistered by providing an encoding for supervisory control of registration and deregistration procedures.



EP 0 952 744 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 3149

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
P, Y	DE 197 19 955 A (DETEMOBIL) 19 November 1998 (1998-11-19) * column 1, line 3 - column 5, line 37 *	1, 8	H04Q7/22 H04Q7/24 H04Q7/38 H04Q3/00
A	US 5 566 235 A (HETZ) 15 October 1996 (1996-10-15) * column 6, line 37 - column 15, line 50; figures *	1, 8	
A	US 5 749 053 A (KUSAKI ET AL.) 5 May 1998 (1998-05-05) * column 5, line 38 - column 19, line 58; figures *	2-5	
P, A	& JP 08 065728 A (HITACHI) 8 March 1996 (1996-03-08)	1, 8, 12	
A	DE 196 32 354 C (E-PLUS MOBILFUNK) 19 February 1998 (1998-02-19) * column 1, line 14 - column 5, line 3; figures *	1, 8, 12	
A	EP 0 793 394 A (SIEMENS) 3 September 1997 (1997-09-03) * page 4, column 5, line 24 - page 5, column 8, line 36; figures *	1, 8, 12	TECHNICAL FIELDS SEARCHED (Int.Cl.6) H04Q
A	EP 0 735 788 A (ALCATEL) 2 October 1996 (1996-10-02) * page 2, column 1, line 3 - page 4, column 5, line 18; figures *	1, 8	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 31 October 2000	Examiner Geoghegan, C
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EP FORM 1500 03.02 (P04.001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 3149

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-10-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19719955 A	19-11-1998	AU 8331998 A	08-12-1998
		WO 9852361 A	19-11-1998
		EP 0981915 A	01-03-2000
		PL 336977 A	31-07-2000
US 5566235 A	15-10-1996	NONE	
US 5749053 A	05-05-1998	JP 8065728 A	08-03-1996
DE 19632354 C	19-02-1998	NONE	
EP 793394 A	03-09-1997	DE 19608464 A	04-09-1997
		CN 1160330 A	24-09-1997
		US 6085105 A	04-07-2000
EP 735788 A	02-10-1996	DE 19511520 A	02-10-1996
		AU 708016 B	29-07-1999
		AU 4806496 A	10-10-1996
		CN 1148295 A	23-04-1997
		JP 8316899 A	29-11-1996
		US 5937350 A	10-08-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

This Page Blank (uspto)